

## Water Temperature Sensors

for cooling systems

TEGV temperature sensors are especially designed for detecting the temperature of cooling water. Sensor is always installed in a pocket of stainless steel (AT80) or brass (ATM80). Housing is made of heat resistant plastics. The screw cover and the terminal blocks tilted to 45° make an easy installation.

Temperature is detected by a range of thermistors and resistive elements with nominal resistances (see table overleaf).

The sensor is installed to the sensor pocket. The pocket is installed to the water pipe by means of threads R1/2". Note that the pocket is required to be ordered separately.



Model Types	Model	Description
	<b>TEGV 1000</b>	PTC1000 Temperature Sensor for Cooling Water
	<b>TEGV PT1000</b>	PT1000 Temperature Sensor for Cooling Water
	<b>TEGV NTC10</b>	NTC10 Temperature Sensor for Cooling Water (Trend, Johnson and Saia equivalent)
	<b>TEGV NTC20</b>	NTC20 Temperature Sensor for Cooling Water (Honeywell equivalent)
	<b>TEGV NTC1800</b>	NTC1800 Temperature Sensor for Cooling Water (TAC equivalent)
	<b>TEGV NI1000-LG</b>	NI1000 Temperature Sensor for Cooling Water (Landis & Staefa equivalent)
	<b>TEGV NTC10-KB</b>	NTC10 Linearised Temperature Sensor for Cooling Water (Satchwell equivalent)
	<b>TEGV NTC-10AN</b>	NTC10-AN Temperature Sensor for Cooling Water (Andover equivalent)
<b>Technical Data</b>	Sensor Element	TEGV 1000 - 1000Ω PTC thermistor TEGV PT1000 - Pt1000 EN 60751/B TEGV NTC10 - 10kΩ NTC thermistor TEGV NTC20 - 20kΩ NTC thermistor TEGV NTC1800 - 1800kΩ NTC thermistor TEGV NI1000-LG - Ni1000-LG TEGV NTC10-KB - Linearised 10kΩ NTC thermistor TEGV NTC10-AN - 10k4A1 NTC thermistor
	Accuracy	TEGV 1000 - ±1.3°C (at 25°C) TEGV PT1000 - ±0.3°C (at 0°C) TEGV NTC10, TEGV NTC20, TEGV NTC10-AN & TEGV NTC1800 - ±0.2°C (at 25°C) TEGV NI1000-LG - ±0.5°C (at 0°C) TEGV NTC10-KB - ±0.3°C (at 25°C)
	Connection	R 1/2", threads (using AT/ATM/ATH pocket)
	Stem (pocket)	Ø8mm x 80mm steel/brass
	Housing	plastic (<120°C)
	Protection class	IP 54, cable entry or stem down
	Cable entry	M16
	Range	-50°C...+120°C
	Pressure rating	PN 16

Temperature/Resistance

°C	PTC1000/Ω	PT1000/Ω	NTC10/Ω	NTC20/Ω	Ni1000-LG/Ω	NTC10-KB/Ω	NTC10-AN/Ω	NTC1800/Ω
120	1923	1460.6	389.0	609	1616.4	466	483	N/A
100	1700	1385.0	680.0	1114	1500.0	721	817	N/A
90	1594	1347.0	917.7	1541	1444.4	921	1084	N/A
80	1492	1308.9	1258.0	2166	1390.1	1193	1458	N/A
75	1442	1289.8	1480.0	2585	1363.5	1364	1700	N/A
70	1394	1270.7	1752.0	3099	1337.1	1563	1990	N/A
65	1347	1251.6	2082.0	3732	1311.1	1792	2339	N/A
60	1300	1232.4	2488.0	4517	1285.4	2056	2760	542
55	1254	1213.2	2968.0	5494	1260.1	2358	3271	634
50	1209	1194.0	3603.0	6718	1235.0	2702	3893	744
45	1166	1174.7	4368.0	8259	1210.2	3089	4656	878
40	1123	1155.4	5327.0	10211	1185.7	3518	5594	1042
35	1081	1136.1	6532.0	12698	1161.5	3987	6754	1243
30	1040	1116.7	8057.0	15887	1137.6	4492	8197	1491
25	1000	1097.3	10000.0	20000	1114.0	5025	10000	1800
20	961	1077.9	12490.0	25350	1090.7	5573	12268	2187
15	923	1058.5	15710.0	32346	1067.6	6125	15136	2675
10	886	1039.0	19900.0	41567	1044.8	6667	18787	3295
5	850	1019.5	25400.0	53812	1022.3	7152	23462	4090
0	815	1000.0	32650.0	70203	1000.0	7661	29490	5117
-5	781	980.4	42340.0	92322	978.0	8093	37316	6456
-10	748	960.9	55330.0	122431	956.2	8472	47549	8217
-15	716	941.2	72980.0	163777	934.7	8796	61030	10556
-20	685	921.6	97070.0	221088	913.5	9067	78930	13696
-25	655	901.9	130400.0	301297	892.5	9288	102890	17959
-30	625	882.2	177000.0	414698	871.7	9465	135233	23811
-40	570	842.7	336500.0	810861	830.8	9711	239831	43409
-50	518	803.1	670100.0	1659082	790.9	N/A	N/A	N/A

Accessories

Model	Description
<b>AT 80</b>	Pocket for TEGV & TEAT sensors, AISI 303 steel
<b>ATH 80</b>	Pocket for TEGV & TEAT sensors, AISI 316L steel
<b>ATM 80</b>	Pocket for TEGV & TEAT sensors, brass MS362

Dimensions

